



Kabeldozen, COMBI 407



COMBI 407



Beschermklasse
Gloeidraadtest
Gebruikstemperatuur
Installatietemperatuur
Spanning
Klemmen/polen
Opmerking
Materiaal

IP 66/67
750 °C
-30 °C - 100 °C
-5 °C - 60 °C
690 V
4 mm²
.../5 = Klemsteen 5-polig
Polypropyleen, inzetstuk TPE

Type	WISKA-No.	RAL-No.	 (mm)		LxBxH external (mm)	
COMBI 407/leer	10105595	RAL 7035	3 · 12		95 x 95 x 60mm	5
COMBI 407/5	10105596	RAL 7035	3 · 12		95 x 95 x 60mm	5
COMBI 407/SDK5	10105597	RAL 7035	3 · 12		95 x 95 x 60mm	5
COMBI 407/leer/W	10105598	RAL 9001	3 · 12		95 x 95 x 60mm	5
COMBI 407/5/W	10105599	RAL 9001	3 · 12		95 x 95 x 60mm	5
COMBI 407/SDK5/W	10105600	RAL 9001	3 · 12		95 x 95 x 60mm	5
COMBI 407/leer/S	10105601	RAL 9005	3 · 12		95 x 95 x 60mm	5
COMBI 407/5/S	10105602	RAL 9005	3 · 12		95 x 95 x 60mm	5
COMBI 407/SDK5/S	10105603	RAL 9005	3 · 12		95 x 95 x 60mm	5
COMBI 407/3X ESKV 20 PLUS	10105969	RAL 7035	3 · 12		95 x 95 x 60mm	5
COMBI 407/S/3X ESKV 20 PLUS	10105978	RAL 9005	3 · 12		95 x 95 x 60mm	5
COMBI 407/W/3X ESKV 20 PLUS	10105977	RAL 9001	3 · 12		95 x 95 x 60mm	5
DIN Rail KIT 407/TS 15	10105604					1
DIN Rail KIT 407/TS 35	10105605					1