

## NSYTBS24198T

ABS box IP66 IK07 RAL7035 Int.H225W175D80  
Ext.H241W194D87 Transp.cover H20



### Main

|                           |                                                     |
|---------------------------|-----------------------------------------------------|
| Range of product          | Thalassa TBS                                        |
| Device application        | Multi-purpose                                       |
| Product or component type | Industrial box                                      |
| Height                    | 241 mm                                              |
| Width                     | 194 mm                                              |
| Depth                     | 87 mm                                               |
| Internal height           | 225 mm                                              |
| Internal width            | 175 mm                                              |
| Internal depth            | 80 mm                                               |
| Enclosure mounting        | Wall mounted                                        |
| Device composition        | 1 x body<br>1 x cover<br>4 x cover screw            |
| Body type                 | One piece moulded                                   |
| Type of front cover       | Low transparent cover                               |
| Cover fixing              | Plastic screws                                      |
| Lock type                 | Outside sealed area: flat screwdriver captive screw |
| Removable parts           | Cover, by captive screws                            |

### Complementary

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Material                              | ABS                                 |
| Colour                                | Grey ( RAL 7035 )<br>Transparent    |
| Standards                             | IEC 62208                           |
| Product certifications                | DEMKO<br>SEMKO<br>TÜV               |
| IP degree of protection               | IP66conforming to NEMA 4.4X         |
| IK degree of protection               | IK07conforming to IEC 62262         |
| Fire resistance                       | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage   | -15...40 °C                         |
| Ambient air temperature for operation | -25...60 °C                         |

### Environment

### Offer Sustainability

|                                  |                                                                       |
|----------------------------------|-----------------------------------------------------------------------|
| Sustainable offer status         | Not Green Premium product                                             |
| RoHS (date code: YYWW)           | Compliant - since 0940 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product end of life instructions | Need no specific recycling operations                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.