


## NSYTBS885

ABS box IP66 IK07 RAL7035 Int.H80W80D65  
Ext.H89W89D51 Opaque cover H10



### Main

|                           |                                                     |
|---------------------------|-----------------------------------------------------|
| Range of product          | Thalassa TBS                                        |
| Device application        | Multi-purpose                                       |
| Product or component type | Industrial box                                      |
| Height                    | 89 mm                                               |
| Width                     | 89 mm                                               |
| Depth                     | 54 mm                                               |
| Internal height           | 80 mm                                               |
| Internal width            | 80 mm                                               |
| Internal depth            | 47 mm                                               |
| Enclosure mounting        | Wall mounted                                        |
| Device composition        | 1 x body<br>1 x cover<br>4 x cover screw            |
| Quantity per set          | Set of 5                                            |
| Body type                 | One piece moulded                                   |
| Type of front cover       | Low plain cover                                     |
| Cover fixing              | Metal screws                                        |
| Lock type                 | Outside sealed area: flat screwdriver captive screw |
| Removable parts           | Cover, by captive screws                            |

### Complementary

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Material                              | ABS                                 |
| Colour                                | Grey ( RAL 7035 )                   |
| Standards                             | IEC 62208                           |
| Product certifications                | DEMKO<br>SEMKO<br>TÜV               |
| IP degree of protection               | IP66conforming to NEMA 4.4X         |
| IK degree of protection               | IK07conforming to IEC 62262         |
| Fire resistance                       | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage   | -15...40 °C                         |
| Ambient air temperature for operation | -25...60 °C                         |

### Environment

### Offer Sustainability

|                                  |                                                                       |
|----------------------------------|-----------------------------------------------------------------------|
| Sustainable offer status         | Not Green Premium product                                             |
| RoHS (date code: YYWW)           | Compliant - since 0940 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product end of life instructions | Need no specific recycling operations                                 |